



| <b>BCS-OCS-M/LED DISPLAY<br/>BCS-OCS-L /LCD DISPLAY<br/>Portable crane Scale</b>   | <b>BCS-OCS-Z<br/>Heavy duty</b>  |
|--|--|
|  <p>Max capacity.<br/>(kg/lb)</p> <p>50kg/100lb<br/>100kg/200lb<br/>200kg/400lb<br/>300kg/600lb<br/>500kg/1000lb<br/>1000kg/2000lb</p>  |  <p>Max capacity.<br/>(kg/lb)</p> <p>10000kg/20000lb<br/>15000kg/30000lb<br/>20000kg/40000lb<br/>30000kg/60000lb<br/>50000kg/100000lb</p>              |
| <b>BCS-OCS-A/LED<br/>BCS-OCS-B/LCD<br/>General</b>   | <b>BCS-OCS-G<br/>Heat proof</b>  |
|  <p>Max capacity<br/>(kg/lb)</p> <p>1000kg/2000lb<br/>2000kg/4000lb<br/>3000kg/6000lb<br/>5000kg/10000lb<br/>10000kg/20000lb<br/>15000kg/30000lb<br/>20000kg/40000lb</p>   |  <p>Max capacity.<br/>(kg/lb)</p> <p>1000kg/2000lb<br/>2000kg/4000lb<br/>3000kg/6000lb<br/>5000kg/10000lb<br/>10000kg/20000lb<br/>15000kg/30000lb</p> |
| <b>BCS-OCS-E<br/>Wireless crane scale</b>  | <b>BCS-OCS-S /LCD DISPLAY<br/>Light Duty Portable<br/>Crane Scale</b>  |
|  <p>Max capacity<br/>(kg/lb)</p> <p>1000kg/2000lb<br/>2000kg/4000lb<br/>3000kg/6000lb<br/>5000kg/10000lb<br/>10000kg/20000lb<br/>15000kg/30000lb<br/>20000kg/40000lb<br/>30000kg/60000lb<br/>50000kg/100000lb</p> |  <p>50kg/100lb<br/>100kg/200lb<br/>200kg/400lb<br/>300kg/600lb</p>  |

**B.C. Scale Company Limited**

5920 - 200 A Street Langley, B.C. Canada, V3A 5X8

Phone(604)534-8633 Fax(604)534-7633

web <http://www.bcscales.com>

**Measurement Canada Weights and Measures Accredited**



## Portable Crane Scales



|                                      |  |
|--------------------------------------|--|
| <b>Features:</b>                     | 30mm(1.2") LCD display Remote control calibration                                |
|                                      | Easy to replace battery pack AC/DC power adaptor output DC9V/1.5A                |
|                                      | 6 V/10Ah rechargeable battery Infrared remote controller, distance 20m           |
|                                      | Hold, tare, accumulation, kg/lb conversion , gross/net conv parameter regulation |
| <b>Accuracy Class:</b>               | OIML Class III   |
| <b>Display:</b>                      | 30mm(1.2") 5 digits LCD  |
| <b>Tare Range:</b>                   | Full capacity  |
| <b>Stable Time:</b>                  | < 10 seconds   |
| <b>Overload Indication:</b>          | 100% Max. capacity + 9e  |
| <b>Max. Safety Load:</b>             | 125% Max. capacity   |
| <b>Ultimate Load:</b>                | 400% Max. capacity   |
| <b>Operation time:</b>               | 60 hours min/100 hours max(depends on operation mode)                            |
| <b>Battery Type:</b>                 | Fully sealed lead-acid battery, 6V/10Ah  |
| <b>Charger:</b>                      | DC9V/1500mA  |
| <b>Operating Temp:</b>               | -10°C - +40°C  |
| <b>Operating Humidity:</b>           | < 85% RH under 20°C  |
| <b>Battery of Remote Controller:</b> | 5# battery, 1.5V x 2   |

### B.C. Scale Company Limited

5920 - 200 A Street Langley, B.C. Canada, V3A 5X8

Phone(604)534-8633 Fax(604)534-7633

web <http://www.bcscales.com>

**Measurement Canada Weights and Measures Accredited**



## General Crane Scale(OCS-A)



|                                      |   |
|--------------------------------------|---|
| <b>Features:</b>                     | 30mm(1.2") LED display  |
|                                      | Remote control calibration  |
|                                      | Easy to replace battery pack AC/DC power adaptor output DC9V/1.5A 6 V/10Ah rechargeable battery |
|                                      | Infrared remote controller, distance 20m  |
|                                      | Hold, tare, accumulation, kg/lb conversion , gross/net conversion parameter regulation          |
| <b>Accuracy Class:</b>               | OIML Class III  |
| <b>Display:</b>                      | 30mm(1.2") 5 digits LCD   |
| <b>Tare Range:</b>                   | Full capacity   |
| <b>Stable Time:</b>                  | <10 seconds   |
| <b>Overload Indication:</b>          | 100% Max. capacity + 9e   |
| <b>Max. Safety Load:</b>             | 125% Max. capacity  |
| <b>Ultimate Load:</b>                | 400% Max. capacity  |
| <b>Operation time:</b>               | 60 hours min/100 hours max  |
| <b>Battery Type:</b>                 | Fully sealed lead-acid battery, 6V/10Ah   |
| <b>Charger:</b>                      | DC9V/1500mA   |
| <b>Operating Temp:</b>               | -10°C - +40°C   |
| <b>Operating Humidity:</b>           | < 85% RH under 20°C   |
| <b>Battery of Remote Controller:</b> | 5# battery, 1.5V x 2  |

### **B.C. Scale Company Limited**

5920 - 200 A Street Langley, B.C. Canada, V3A 5X8

Phone(604)534-8633 Fax(604)534-7633

web <http://www.bcscales.com>

**Measurement Canada Weights and Measures Accredited**



## Heavy Duty Crane Scales



|                                      |   |
|--------------------------------------|---|
| <b>Features:</b>                     | All steel armour-clad enclosure, crashworthy and anticorr             |
|                                      | 56mm LED display, over 30m visual range                               |
|                                      | High accuracy steel alloy load cell for stable and reliable measuring |
|                                      | Quality steel alloy load receptor against ultimate load of c 500% F.S |
|                                      | Considerable capacity long life rechargeable battery                  |
|                                      | Remote controller, easy-to-use and convenient                         |
| <b>Accuracy Class:</b>               | OIML Class III  |
| <b>Display:</b>                      | 30mm(1.2") 5 digits LCD   |
| <b>Tare Range:</b>                   | Full capacity   |
| <b>Stable Time:</b>                  | < 10 seconds  |
| <b>Overload Indication:</b>          | 100% Max. capacity + 9e   |
| <b>Max. Safety Load:</b>             | 125% Max. capacity  |
| <b>Ultimate Load:</b>                | 400% Max. capacity  |
| <b>Operation time:</b>               | 60 hours min/100 hours max(depends on operation mode)                 |
| <b>Battery Type:</b>                 | Fully sealed lead-acid battery, 6V/10Ah                               |
| <b>Charger:</b>                      | DC9V/1500mA   |
| <b>Operating Temp:</b>               | -10°C - +40°C   |
| <b>Operating Humidity:</b>           | < 85% RH under 20°C   |
| <b>Battery of Remote Controller:</b> | 5# battery, 1.5V x 2  |

### B.C. Scale Company Limited

5920 - 200 A Street Langley, B.C. Canada, V3A 5X8

Phone(604)534-8633 Fax(604)534-7633

web <http://www.bcscales.com>

**Measurement Canada Weights and Measures Accredited**



## Light Duty Portable Crane Scales



|                  |   |
|------------------|---|
| <b>Capacity:</b> | 30-300kg  |
| <b>Function:</b> | Tare. Zero Hold. Low-voltage auto-power off. Overload alarm |
|                  | N/kg/lb conversion/ Battery supervision                     |
|                  | Aluminum-die casting enclosure                              |
|                  | with S.S hook and shackle                                   |
|                  | 20mm LCD display  |
|                  | with internal battery                                       |
|                  | Waterproof panel button                                     |

### **B.C. Scale Company Limited**

5920 - 200 A Street Langley, B.C. Canada, V3A 5X8

Phone(604)534-8633 Fax(604)534-7633

web <http://www.bcscales.com>

**Measurement Canada Weights and Measures Accredited**



## Wireless Crane Scales



|                                      |  |
|--------------------------------------|--|
| <b>Features:</b>                     | Data wireless transmission               |
|                                      | Internal clocks and calendar             |
|                                      | Multilane print format                   |
|                                      | Division selection                       |
|                                      | Easy to replace battery pack             |
|                                      | High-tension hook and shackle            |
| <b>Accuracy Class:</b>               | According to OIML III                    |
| <b>Display:</b>                      | 25mm high, 6 digits screen digits tube   |
| <b>Tare Range:</b>                   | 100% F.S.                                |
| <b>Stable Time:</b>                  | ≤10 seconds                              |
| <b>Overload Indication:</b>          | 100% F.S. + 9e                           |
| <b>Max. Safety Load:</b>             | 125% F.S.                                |
| <b>Ultimate Load:</b>                | 400%F.S.                                 |
| <b>Operation time:</b>               | ≥50 hours                                |
| <b>Battery Type:</b>                 | 12V/7Ah full sealed rechargeable battery |
| <b>Charger:</b>                      | AC220V/DC12V1500mA                       |
| <b>Operating Temp:</b>               | -10°C - +40°C                            |
| <b>Operating Humidity:</b>           | < 90% RH at 20°C                         |
| <b>Battery of Remote Controller:</b> | 5# battery, 1.5V x 2                     |

### B.C. Scale Company Limited

5920 - 200 A Street Langley, B.C. Canada, V3A 5X8

Phone(604)534-8633 Fax(604)534-7633

web <http://www.bcscales.com>

**Measurement Canada Weights and Measures Accredited**

## Heat Proof Crane Scales



|                                      |  |
|--------------------------------------|--|
| <b>Features:</b>                     | 30mm(1.2") LCD display Remote control calibration  |
|                                      | Easy to replace battery pack AC/DC power adaptor output DC9V/1.5A                        |
|                                      | 6 V/10Ah rechargeable battery Infrared remote controller, distance 20m                   |
|                                      | Hold, tare, accumulation, kg/lb conversion , gross/net conversion , parameter regulation |
| <b>Accuracy Class :</b>              | OIML Class III   |
| <b>Display:</b>                      | 30mm(1.2") 5 digits LCD  |
| <b>Tare Range :</b>                  | Full capacity  |
| <b>Stable Time :</b>                 | < 10 seconds   |
| <b>Overload Indication:</b>          | 100% Max. capacity + 9e  |
| <b>Max. Safety Load:</b>             | 125% Max. capacity   |
| <b>Ultimate Load:</b>                | 400% Max. capacity   |
| <b>Operation time:</b>               | 60 hours min/100 hours max(depends on operation mode)                                    |
| <b>Battery Type:</b>                 | Fully sealed lead-acid battery, 6V/10Ah  |
| <b>Charger:</b>                      | DC9V/1500mA  |
| <b>Operating Temp:</b>               | -10°C - +40°C  |
| <b>Operating Humidity:</b>           | < 85% RH under 20°C  |
| <b>Battery of Remote Controller:</b> | 5# battery, 1.5V x 2   |

### **B.C. Scale Company Limited**

5920 - 200 A Street Langley, B.C. Canada, V3A 5X8

Phone(604)534-8633 Fax(604)534-7633

web <http://www.bcscales.com>

**Measurement Canada Weights and Measures Accredited**